

Eaton Wash Down EC116



# Part number	Hose ID			Hose OD		Max. Operating pressure		Burst pressure		Max. Bending radius		Weight	
	DN	mm	in	mm	in	bar	psi	bar	psi	mm	in	kg/m	lb/ft
EC116-04BU	6	6.4	0.25	12.2	0.48	250	3625	1000	14500	75	2.94	0.18	0.13
EC116-05BU	8	7.9	0.31	13.6	0.54	250	3625	1000	14500	85	3.34	0.2	0.14
EC116-06BU	10	9.5	0.38	15.5	0.61	250	3625	1000	14500	90	3.53	0.26	0.18
EC116-08BU	12	12.7	0.5	19	0.75	250	3625	1000	14500	130	5.1	0.345	0.24

*Product also available in GY-Gray

Construction

- Synthetic rubber tube
- One wire braid reinforcement
- Oil, abrasion and weather resistant special synthetic rubber smooth cover
- Embossed layline
- Available in blue or grey color cover

Operating temperature

- 40°C to +150°C (intermittent)*
- 40°F to +302°F (intermittent)

Application

High pressure cleaners for food, car wash, labor and swimming bath areas

Approved fittings

- TTC series
- * For pressure washer application only


SUTTER
HYDRAULIK & PNEUMATIK AG
 Hauptstrasse 7 · CH-4455 Zuzgen
 Telefon +41 (0)61 836 90 70 · Telefax +41 (0)61 836 90 71
 info@sutter-hydraulik.com · www.sutter-hydraulik.com

Eaton
 EMEA Headquarters
 Route de la Longeraie 7
 1110 Morges, Switzerland
 Eaton.eu

© 2017 Eaton
 All Rights Reserved
 Printed in USA
 Publication No. CAXXXXXXXXXX / XXX
 April 2017

Eaton
 Hydraulics Group USA
 14615 Lone Oak Road
 Eden Prairie, MN 55344
 USA
 Tel: 952-937-9800
 Fax: 952-294-7722
 www.eaton.com/hydraulics

Eaton
 Hydraulics Group Europe
 Route de la Longeraie 7
 1110 Morges
 Switzerland
 Tel: +41 (0) 21 811 4600
 Fax: +41 (0) 21 811 4601


 Powering Business Worldwide