

Eaton Wash Down EC216



# Part number	Hose ID			Hose OD		Max. Operating pressure		Burst pressure		Max. Bending radius		Weight	
	DN	mm	in	mm	in	bar	psi	bar	psi	mm	in	kg/m	lb/ft
EC216-04BU	6	6.4	0.25	13.4	0.53	400	5800	1600	23200	75	2.94	0.285	0.20
EC216-05BU	8	7.9	0.31	15	0.59	400	5800	1600	23200	85	3.34	0.335	0.23
EC216-06BU	10	9.5	0.38	17.1	0.67	400	5800	1600	23200	90	3.53	0.42	0.29
EC216-08BU	12	12.7	0.5	20.7	0.81	400	5800	1600	23200	130	5.1	0.575	0.40

*Product also available in GY-Gray

Construction

- Synthetic rubber tube
- Two wire braids reinforcement
- Oil, abrasion and weather resistant special synthetic rubber smooth cover
- Embossed layline
- Available in blue or grey color cover

Operating temperature

- 40°C to +150°C (intermittent)*
- 40°F to +302°F (intermittent)

Application

High pressure cleaners for food, car wash, labor and swimming bath areas

Approved fittings

- TTC series
- * For pressure washer application only

HYDRAULIK & PNEUMATIK AG

Hauptstrasse 7 - CH-4455 Zuzgen

Telefon +41 (0)61 836 90 70 - Telefax +41 (0)61 836 90 71
info@sutter-hydraulik.com - www.sutter-hydraulik.com

Eaton

EMEA Headquarters
Route de la Longeraie 7
1110 Morges, Switzerland
Eaton.eu

© 2017 Eaton
All Rights Reserved
Printed in USA
Publication No. CAXXXXXXXXXX / XXX
April 2017

Eaton
Hydraulics Group USA
14615 Lone Oak Road
Eden Prairie, MN 55344
USA
Tel: 952-937-9800
Fax: 952-294-7722
www.eaton.com/hydraulics

Eaton
Hydraulics Group Europe
Route de la Longeraie 7
1110 Morges
Switzerland
Tel: +41 (0) 21 811 4600
Fax: +41 (0) 21 811 4601

Powering Business Worldwide