

HW210



Heisswasserschlauch HW210

Innenschicht:
Aussenschicht:
Einlage:
Temperaturbereich: von -40 °C bis +150 °C

Anwendung: Heisswasserreinigung,
Hochdruck-Waschgeräte
Synthetischer Gummi, hochtemperaturbeständig
Synthetischer Gummi, geprickt
ein Stahldrahtgeflecht

Hot water hose HW 210

Inner tube:
Outer cover:
Reinforcement:
Temperature range:

Application: hot water cleaning
High-pressure jet cleaners
synthetic rubber, high temperature resistant
synthetic rubber, pin-pricked
one wire braid
from -40 °C up to +150 °C

Aussendecke: Schwarz

Outer cover: black

DN	Inch	d ₁	d ₂	Biege- radius	Zulässiger Betriebs- überdruck	Prüfdruck	Berst- druck	Gew.	Bestell- nummer
		mm	mm	<i>bend radius</i>	<i>maximum working pressure</i>	<i>proof pressure</i>	<i>burst pressure</i>	<i>weight</i>	<i>Order No.</i>
		mm	mm	mm	bar	bar	bar	kg/m	
6	1/4"	6,6	14,0	100	210	420	840	0,215	A48 13 00
8	5/16"	8,1	15,5	110	210	420	840	0,260	A48 13 01
10	3/8"	9,7	17,5	120	210	420	840	0,340	A48 13 02
12	1/2"	12,7	21,0	160	150	300	600	0,415	A48 13 03

Aussendecke: Blau

Outer cover: blue

DN	Inch	d ₁	d ₂	Biege- radius	Zulässiger Betriebs- überdruck	Prüfdruck	Berst- druck	Gew.	Bestell- nummer
		mm	mm	<i>bend radius</i>	<i>maximum working pressure</i>	<i>proof pressure</i>	<i>burst pressure</i>	<i>weight</i>	<i>Order No.</i>
		mm	mm	mm	bar	bar	bar	kg/m	
6	1/4"	6,6	14,0	100	210	420	840	0,215	A48 13 04
8	5/16"	8,1	15,5	110	210	420	840	0,260	A48 13 05
10	3/8"	9,7	17,5	120	210	420	840	0,340	A48 13 06
12	1/2"	12,7	21,0	160	150	300	600	0,415	A48 13 07

Aussendecke: Grau

Outer cover: grey

DN	Inch	d ₁	d ₂	Biege- radius	Zulässiger Betriebs- überdruck	Prüfdruck	Berst- druck	Gew.	Bestell- nummer
		mm	mm	<i>bend radius</i>	<i>maximum working pressure</i>	<i>proof pressure</i>	<i>burst pressure</i>	<i>weight</i>	<i>Order No.</i>
		mm	mm	mm	bar	bar	bar	kg/m	
6	1/4"	6,6	14,0	100	210	420	840	0,215	A48 13 08
8	5/16"	8,1	15,5	110	210	420	840	0,260	A48 13 09
10	3/8"	9,7	17,5	120	210	420	840	0,340	A48 13 10
12	1/2"	12,7	21,0	160	150	300	600	0,415	A48 13 11

HW400



Heisswasserschlauch HW400

Innenschicht:
Aussenschicht:
Einlage:
Temperaturbereich: von -40 °C bis +150 °C

Anwendung: Heisswasserreinigung,
Hochdruck-Waschgeräte
Synthetischer Gummi, hochtemperaturbeständig
Synthetischer Gummi, geprickt
zwei Stahldrahtgeflechte

Hot water hose HW 400

Inner tube:
Outer cover:
Reinforcement:
Temperature range:

Application: hot water cleaning
High-pressure jet cleaners
synthetic rubber, high temperature resistant
synthetic rubber, pin-pricked
two wire braids
from -40 °C up to +150 °C

Aussendecke: Schwarz

Outer cover: black

DN	Inch	d ₁	d ₂	Biege- radius <i>bend radius</i>	Zulässiger Betriebs- überdruck <i>maximum working pressure</i>	Prüfdruck <i>proof pressure</i>	Berst- druck <i>burst pressure</i>	Gew. <i>weight</i>	Bestell- nummer <i>Order No.</i>
		mm	mm	mm	bar	bar	bar	kg/m	
6	1/4"	6,6	15,5	100	400	800	1600	0,235	A48 13 12
8	5/16"	8,1	16,5	110	400	800	1600	0,275	A48 13 13
10	3/8"	9,7	19,5	120	400	800	1600	0,356	A48 13 14
12	1/2"	12,7	22,5	160	300	600	1200	0,430	A48 13 15

Aussendecke: Blau

Outer cover: blue

DN	Inch	d ₁	d ₂	Biege- radius <i>bend radius</i>	Zulässiger Betriebs- überdruck <i>maximum working pressure</i>	Prüfdruck <i>proof pressure</i>	Berst- druck <i>burst pressure</i>	Gew. <i>weight</i>	Bestell- nummer <i>Order No.</i>
		mm	mm	mm	bar	bar	bar	kg/m	
6	1/4"	6,6	15,5	100	400	800	1600	0,235	A48 13 16
8	5/16"	8,1	16,5	110	400	800	1600	0,275	A48 13 17
10	3/8"	9,7	19,5	120	400	800	1600	0,356	A48 13 18
12	1/2"	12,7	22,5	160	300	600	1200	0,430	A48 13 19

Aussendecke: Grau

Outer cover: grey

DN	Inch	d ₁	d ₂	Biege- radius <i>bend radius</i>	Zulässiger Betriebs- überdruck <i>maximum working pressure</i>	Prüfdruck <i>proof pressure</i>	Berst- druck <i>burst pressure</i>	Gew. <i>weight</i>	Bestell- nummer <i>Order No.</i>
		mm	mm	mm	bar	bar	bar	kg/m	
6	1/4"	6,6	15,5	100	400	800	1600	0,235	A48 13 20
8	5/16"	8,1	16,5	110	400	800	1600	0,275	A48 13 21
10	3/8"	9,7	19,5	120	400	800	1600	0,356	A48 13 22
12	1/2"	12,7	22,5	160	300	600	1200	0,430	A48 13 23